



1" Cam Buckle | SpanSet

Utility rated tiedowns are designed for farm, automotive, utility marine, light truck and industrial uses

Item Name short	Assembly Type	Weight Net [lbs]	Length [ft.]	End Fitting Component
20B5S	Two-piece	2	5	SH-PVC-1"
20B9JK	Two-piece	2	9	JH-K-1"
20B12JK	Two-piece	2	12	JH-K-1"
20B12S	Two-piece	2	12	SH-PVC-1"
20B12E	One-piece	2	12	Endless
25B12JK	Two-piece	2	12	JH-K-1"
25B12S	Two-piece	2	12	SH-PVC-1"
25B12E	One-piece	2	12	Endless
20B20JK	Two-piece	2	20	JH-K-1"
20B20S	Two-piece	2	20	SH-PVC-1"
20B20E	One-piece	2	20	Endless
25B20JK	Two-piece	2	20	JH-K-1"
25B20S	Two-piece	2	20	SH-PVC-1"
25B20E	One-piece	2	20	Endless
25B5S	Two-piece	2.2	5	SH-PVC-1"
25B9JK	Two-piece	2.2	9	JH-K-1"



ORDER NUMBERS[Global Item Number/Local ERP Number SSUS]

End Fitting Component	5 ft.	9 ft.	12 ft.	20 ft.
 Endless	-	-	2014615 20B12E,2014625 25B12E	2014616 20B20E,2014626 25B20E
 JH-K-1"	-	2014609 20B9JK	2014610 20B12JK	2014617 20B20JK
 SH-PVC-1"	2014613 20B5S	-	2014614 20B12S	2014618 20B20S
 JH-K-1"	-	2014619 25B9JK	2014620 25B12JK	2014621 25B20JK
 SH-PVC-1"	2014622 25B5S	-	2014623 25B12S	2014624 25B20S

- Webbing Material Polyester
- Webbing Width B 1 in
- Temperature Range -40° TO + 194°
- Packaging Unit (PU) Content 1

SpanSet, Inc.
3125 Industrial Drive
Sanford, NC 27331
United States of
America
800-334-7505
info@spanset.com
www.spanset.com



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet, Inc. - USA

**SpanSet
Certified
Safety**