



Heavy Duty Recovery Tow Straps

Made of high tenacity polyester or nylon material and are available up to 180,000 lbs. on special request

Item Name short	Lashing Capacity [lbs]	Weight Net [lbs]	Length [ft.]	Width [in]	Main Material
RS4830N	-	2	30	6	Nylon
RS3230N	10667	1.5	30	4	Nylon
RS3230	10667	2	30	4	Polyester
RS4830	16000	2	30	6	Polyester
RS8230	27333	2	30	6	Polyester
RS8230N	27333	2	30	6	Nylon
RS8250	27333	2	50	6	Polyester

ORDER NUMBERS[Global Item Number/Local ERP Number SSUS]

Length	Nylon	Polyester
30 ft.	-	2014634 RS3230,2014636 RS4830,2014637 RS8230
30 ft.	2014646 RS3230N	-
30 ft.	2014648 RS4830N	-
30 ft.	2014649 RS8230N	-
50 ft.	-	2014638 RS8250

- Temperature Range -40° C to + 50° C
- Temperature Range -40 °F to 120 °F
- Packaging Unit (PU) Content 1

SpanSet, Inc.
3125 Industrial Drive
Sanford, NC 27331
United States of
America
800-334-7505
info@spanset.com
www.spanset.com



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet, Inc. - USA

**SpanSet
Certified
Safety**