

PowerLift Type 3 (EE) Flat Eye & Eye Web Sling

SpanSet PowerLift Web Slings - Type 3 (EE) – Flat Eye & Eye Lifting Sling

Item Name short	Weight Net [lbs]	WLL Vertical [lbs]	Length [ft.]	WLL Choker [lbs]	WLL 90° Basket lbs [lbs]	Belt Layers	Minimum Length [ft.]
EE2701X4P	0.33	3100	4	2480	6200	2	3
EE2701X3	0.4	3100	3	2480	6200	2	3
EE2701X6P	0.48	3100	6	2480	6200	2	3
EE1701X3	0.6	1600	3	1280	3200	-	3
EE2701X8P	0.65	3100	8	2480	6200	2	3
EE1702X3	0.65	3200	3	2560	6400	-	3
EE1701X4	0.73	1600	4	1280	3200	-	3
EE1702X4	0.78	3200	4	2560	6400	-	3
EE2701X6	0.8	3100	6	2480	6200	2	3
EE1701X6	0.85	1600	6	1280	3200	-	3
EE2702X3	0.86	6400	3	5120	12800	-	6
EE2702X3P	0.86	6400	3	5120	12800	2	6
EE1702X6	0.9	3200	6	2560	6400	-	3
EE2702X4P	0.94	6400	4	5120	12800	2	6
EE1701X10	0.98	1600	10	1280	3200	-	3
EE2701X10	1.35	3100	10	2480	6200	2	3
EE1702X10	1.35	3200	10	2560	6400	-	3
EE2702X6P	1.38	6400	6	5120	12800	2	6
EE2702X6	1.55	6400	6	5120	12800	-	6
EE2702X8P	1.84	6400	8	5120	12800	2	6
EE2704X4P	1.88	11500	4	9200	23000	2	-
EE2703X4P	1.92	9300	4	7400	18600	2	-
EE2702X10P	2.5	6400	10	5120	12800	2	6
EE2704X6	2.65	11500	6	9200	23000	-	6
EE2704X6P	2.82	11500	6	9200	23000	2	-
EE2703X6P	2.88	9300	6	7400	18600	2	-
EE2702X12	2.9	6400	12	5120	12800	-	6
EE2702X12P	2.9	6400	12	5120	12800	2	6
EE2704X10	3.65	11500	10	9200	23000	-	6
EE2702X16P	3.68	6400	16	5120	12800	2	6
EE2703X8P	3.84	9300	8	7400	18600	2	-



Item Name short	Weight Net [lbs]	WLL Vertical [lbs]	Length [ft.]	WLL Choker [lbs]	WLL 90° Basket lbs [lbs]	Belt Layers	Minimum Length [ft.]
EE2702X20P	4.5	6400	20	5120	12800	2	6
EE2704X10P	4.7	11500	10	9200	23000	2	-
EE2703X10P	4.8	9300	10	7400	18600	2	-
EE2704X12P	5.64	11500	12	9200	23000	2	-
EE2703X12P	5.76	9300	12	7400	18600	2	-
EE2703X16P	7.68	9300	16	7400	18600	2	-
EE2704X20P	9.4	11500	20	9200	23000	2	-
EE2703X20P	9.6	9300	20	7400	18600	2	-

Item Name short	Minimum Eye Length [in]	Width [in]	Main Material
EE2701X4P	12	1	Polyester
EE2701X3	12	1	Nylon
EE2701X6P	12	1	Polyester
EE1701X3	12	1	Nylon
EE2701X8P	12	1	Polyester
EE1702X3	12	2	Nylon
EE1701X4	12	1	Nylon
EE1702X4	12	2	Nylon
EE2701X6	12	1	Nylon
EE1701X6	12	1	Nylon
EE2702X3	12	2	Nylon
EE2702X3P	12	2	Polyester
EE1702X6	12	2	Nylon
EE2702X4P	12	2	Polyester
EE1701X10	12	1	Nylon
EE2701X10	12	1	Nylon
EE1702X10	12	2	Nylon
EE2702X6P	12	2	Polyester
EE2702X6	12	2	Nylon
EE2702X8P	12	2	Polyester
EE2704X4P	23	4	Polyester



Item Name short	Minimum Eye Length [in]	Width [in]	Main Material
EE2703X4P	20	3	Polyester
EE2702X10P	12	2	Polyester
EE2704X6	23	4	Nylon
EE2704X6P	23	4	Polyester
EE2703X6P	20	3	Polyester
EE2702X12	12	2	Nylon
EE2702X12P	12	2	Polyester
EE2704X10	23	4	Nylon
EE2702X16P	12	2	Polyester
EE2703X8P	20	3	Polyester
EE2702X20P	12	2	Polyester
EE2704X10P	23	4	Polyester
EE2703X10P	20	3	Polyester
EE2704X12P	23	4	Polyester
EE2703X12P	20	3	Polyester
EE2703X16P	20	3	Polyester
EE2704X20P	23	4	Polyester
EE2703X20P	20	3	Polyester



ORDER NUMBERS[Global Item Number/Local ERP Number SSUS]

Length	WLL Vertical	Nylon	Polyester
3 ft.	1600 lbs	2024490 EE1701X3	-
3 ft.	3100 lbs	2024515 EE2701X3	-
3 ft.	3200 lbs	2024511 EE1702X3	-
3 ft.	6400 lbs	2024518 EE2702X3	2024675 EE2702X3P
4 ft.	1600 lbs	2024491 EE1701X4	-
4 ft.	3100 lbs	-	2027457 EE2701X4P
4 ft.	3200 lbs	2024512 EE1702X4	-
4 ft.	6400 lbs	-	2027462 EE2702X4P
4 ft.	9300 lbs	-	2027464 EE2703X4P
4 ft.	11500 lbs	-	2027471 EE2704X4P
6 ft.	1600 lbs	2024492 EE1701X6	-
6 ft.	3100 lbs	2024516 EE2701X6	2027458 EE2701X6P
6 ft.	3200 lbs	2024513 EE1702X6	-
6 ft.	6400 lbs	2024519 EE2702X6	2024522 EE2702X6P
6 ft.	9300 lbs	-	2027465 EE2703X6P
6 ft.	11500 lbs	2024525 EE2704X6	2027472 EE2704X6P
8 ft.	3100 lbs	-	2027459 EE2701X8P
8 ft.	6400 lbs	-	2027463 EE2702X8P
8 ft.	9300 lbs	-	2027466 EE2703X8P
10 ft.	1600 lbs	2024493 EE1701X10	-
10 ft.	3100 lbs	2024517 EE2701X10	-

SpanSet, Inc.
3125 Industrial Drive
Sanford, NC 27331
United States of
America
800-334-7505
info@spanset.com
www.spanset.com



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet, Inc. - USA

**SpanSet
Certified
Safety**

Length	WLL Vertical	Nylon	Polyester
10 ft.	3200 lbs	2024514 EE1702X10	-
10 ft.	6400 lbs	-	2024523 EE2702X10P
10 ft.	9300 lbs	-	2027467 EE2703X10P
10 ft.	11500 lbs	2024526 EE2704X10	2027473 EE2704X10P
12 ft.	6400 lbs	2024521 EE2702X12	2024524 EE2702X12P
12 ft.	9300 lbs	-	2027468 EE2703X12P
12 ft.	11500 lbs	-	2027474 EE2704X12P
16 ft.	6400 lbs	-	2027460 EE2702X16P
16 ft.	9300 lbs	-	2027469 EE2703X16P
20 ft.	6400 lbs	-	2027461 EE2702X20P
20 ft.	9300 lbs	-	2027470 EE2703X20P
20 ft.	11500 lbs	-	2027475 EE2704X20P

- **Color** Yellow
- **Temperature Range** -40°C bis +100°C
- **Packaging Unit (PU) Content** 1

SpanSet, Inc.
3125 Industrial Drive
Sanford, NC 27331
United States of
America
800-334-7505
info@spanset.com
www.spanset.com



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet, Inc. - USA

**SpanSet
Certified
Safety**