

PowerLift Type 3 (EE) Flat Eye & Eye Web Sling

SpanSet PowerLift Web Slings - Type 3 (EE) – Flat Eye & Eye Lifting Sling

| Item Name short | Weight Net [lbs] | WLL Vertical [lbs] | Length [ft.] | WLL Choker [lbs] | WLL 90° Basket lbs [lbs] | Belt Layers | Minimum Length [ft.] |
|-----------------|------------------|--------------------|--------------|------------------|--------------------------|-------------|----------------------|
| EE2701X4P | 0.33 | 3100 | 4 | 2480 | 6200 | 2 | 3 |
| EE2701X3 | 0.4 | 3100 | 3 | 2480 | 6200 | 2 | 3 |
| EE2701X6P | 0.48 | 3100 | 6 | 2480 | 6200 | 2 | 3 |
| EE1701X3 | 0.6 | 1600 | 3 | 1280 | 3200 | - | 3 |
| EE2701X8P | 0.65 | 3100 | 8 | 2480 | 6200 | 2 | 3 |
| EE1702X3 | 0.65 | 3200 | 3 | 2560 | 6400 | - | 3 |
| EE1701X4 | 0.73 | 1600 | 4 | 1280 | 3200 | - | 3 |
| EE1702X4 | 0.78 | 3200 | 4 | 2560 | 6400 | - | 3 |
| EE2701X6 | 0.8 | 3100 | 6 | 2480 | 6200 | 2 | 3 |
| EE1701X6 | 0.85 | 1600 | 6 | 1280 | 3200 | - | 3 |
| EE2702X3 | 0.86 | 6400 | 3 | 5120 | 12800 | - | 6 |
| EE2702X3P | 0.86 | 6400 | 3 | 5120 | 12800 | 2 | 6 |
| EE1702X6 | 0.9 | 3200 | 6 | 2560 | 6400 | - | 3 |
| EE2702X4P | 0.94 | 6400 | 4 | 5120 | 12800 | 2 | 6 |
| EE1701X10 | 0.98 | 1600 | 10 | 1280 | 3200 | - | 3 |
| EE2701X10 | 1.35 | 3100 | 10 | 2480 | 6200 | 2 | 3 |
| EE1702X10 | 1.35 | 3200 | 10 | 2560 | 6400 | - | 3 |
| EE2702X6P | 1.38 | 6400 | 6 | 5120 | 12800 | 2 | 6 |
| EE2702X6 | 1.55 | 6400 | 6 | 5120 | 12800 | - | 6 |
| EE2702X8P | 1.84 | 6400 | 8 | 5120 | 12800 | 2 | 6 |
| EE2704X4P | 1.88 | 11500 | 4 | 9200 | 23000 | 2 | - |
| EE2703X4P | 1.92 | 9300 | 4 | 7400 | 18600 | 2 | - |
| EE2702X10P | 2.5 | 6400 | 10 | 5120 | 12800 | 2 | 6 |
| EE2704X6 | 2.65 | 11500 | 6 | 9200 | 23000 | - | 6 |
| EE2704X6P | 2.82 | 11500 | 6 | 9200 | 23000 | 2 | - |
| EE2703X6P | 2.88 | 9300 | 6 | 7400 | 18600 | 2 | - |
| EE2702X12 | 2.9 | 6400 | 12 | 5120 | 12800 | - | 6 |
| EE2702X12P | 2.9 | 6400 | 12 | 5120 | 12800 | 2 | 6 |
| EE2704X10 | 3.65 | 11500 | 10 | 9200 | 23000 | - | 6 |
| EE2702X16P | 3.68 | 6400 | 16 | 5120 | 12800 | 2 | 6 |
| EE2703X8P | 3.84 | 9300 | 8 | 7400 | 18600 | 2 | - |



| Item Name short | Weight Net [lbs] | WLL Vertical [lbs] | Length [ft.] | WLL Choker [lbs] | WLL 90° Basket lbs [lbs] | Belt Layers | Minimum Length [ft.] |
|-----------------|------------------|--------------------|--------------|------------------|--------------------------|-------------|----------------------|
| EE2702X20P | 4.5 | 6400 | 20 | 5120 | 12800 | 2 | 6 |
| EE2704X10P | 4.7 | 11500 | 10 | 9200 | 23000 | 2 | - |
| EE2703X10P | 4.8 | 9300 | 10 | 7400 | 18600 | 2 | - |
| EE2704X12P | 5.64 | 11500 | 12 | 9200 | 23000 | 2 | - |
| EE2703X12P | 5.76 | 9300 | 12 | 7400 | 18600 | 2 | - |
| EE2703X16P | 7.68 | 9300 | 16 | 7400 | 18600 | 2 | - |
| EE2704X20P | 9.4 | 11500 | 20 | 9200 | 23000 | 2 | - |
| EE2703X20P | 9.6 | 9300 | 20 | 7400 | 18600 | 2 | - |

| Item Name short | Minimum Eye Length [in] | Width [in] | Main Material |
|-----------------|-------------------------|------------|---------------|
| EE2701X4P | 12 | 1 | Polyester |
| EE2701X3 | 12 | 1 | Nylon |
| EE2701X6P | 12 | 1 | Polyester |
| EE1701X3 | 12 | 1 | Nylon |
| EE2701X8P | 12 | 1 | Polyester |
| EE1702X3 | 12 | 2 | Nylon |
| EE1701X4 | 12 | 1 | Nylon |
| EE1702X4 | 12 | 2 | Nylon |
| EE2701X6 | 12 | 1 | Nylon |
| EE1701X6 | 12 | 1 | Nylon |
| EE2702X3 | 12 | 2 | Nylon |
| EE2702X3P | 12 | 2 | Polyester |
| EE1702X6 | 12 | 2 | Nylon |
| EE2702X4P | 12 | 2 | Polyester |
| EE1701X10 | 12 | 1 | Nylon |
| EE2701X10 | 12 | 1 | Nylon |
| EE1702X10 | 12 | 2 | Nylon |
| EE2702X6P | 12 | 2 | Polyester |
| EE2702X6 | 12 | 2 | Nylon |
| EE2702X8P | 12 | 2 | Polyester |
| EE2704X4P | 23 | 4 | Polyester |



| Item Name short | Minimum Eye Length [in] | Width [in] | Main Material |
|-----------------|-------------------------|------------|---------------|
| EE2703X4P | 20 | 3 | Polyester |
| EE2702X10P | 12 | 2 | Polyester |
| EE2704X6 | 23 | 4 | Nylon |
| EE2704X6P | 23 | 4 | Polyester |
| EE2703X6P | 20 | 3 | Polyester |
| EE2702X12 | 12 | 2 | Nylon |
| EE2702X12P | 12 | 2 | Polyester |
| EE2704X10 | 23 | 4 | Nylon |
| EE2702X16P | 12 | 2 | Polyester |
| EE2703X8P | 20 | 3 | Polyester |
| EE2702X20P | 12 | 2 | Polyester |
| EE2704X10P | 23 | 4 | Polyester |
| EE2703X10P | 20 | 3 | Polyester |
| EE2704X12P | 23 | 4 | Polyester |
| EE2703X12P | 20 | 3 | Polyester |
| EE2703X16P | 20 | 3 | Polyester |
| EE2704X20P | 23 | 4 | Polyester |
| EE2703X20P | 20 | 3 | Polyester |



ORDER NUMBERS

| Length | WLL Vertical | Nylon | Polyester |
|--------|--------------|---------|-----------|
| 3 ft. | 1600 lbs | 2024490 | - |
| 3 ft. | 3100 lbs | 2024515 | - |
| 3 ft. | 3200 lbs | 2024511 | - |
| 3 ft. | 6400 lbs | 2024518 | 2024675 |
| 4 ft. | 1600 lbs | 2024491 | - |
| 4 ft. | 3100 lbs | - | 2027457 |
| 4 ft. | 3200 lbs | 2024512 | - |
| 4 ft. | 6400 lbs | - | 2027462 |
| 4 ft. | 9300 lbs | - | 2027464 |
| 4 ft. | 11500 lbs | - | 2027471 |
| 6 ft. | 1600 lbs | 2024492 | - |
| 6 ft. | 3100 lbs | 2024516 | 2027458 |
| 6 ft. | 3200 lbs | 2024513 | - |
| 6 ft. | 6400 lbs | 2024519 | 2024522 |
| 6 ft. | 9300 lbs | - | 2027465 |
| 6 ft. | 11500 lbs | 2024525 | 2027472 |
| 8 ft. | 3100 lbs | - | 2027459 |
| 8 ft. | 6400 lbs | - | 2027463 |
| 8 ft. | 9300 lbs | - | 2027466 |
| 10 ft. | 1600 lbs | 2024493 | - |
| 10 ft. | 3100 lbs | 2024517 | - |
| 10 ft. | 3200 lbs | 2024514 | - |
| 10 ft. | 6400 lbs | - | 2024523 |
| 10 ft. | 9300 lbs | - | 2027467 |
| 10 ft. | 11500 lbs | 2024526 | 2027473 |
| 12 ft. | 6400 lbs | 2024521 | 2024524 |
| 12 ft. | 9300 lbs | - | 2027468 |
| 12 ft. | 11500 lbs | - | 2027474 |
| 16 ft. | 6400 lbs | - | 2027460 |
| 16 ft. | 9300 lbs | - | 2027469 |
| 20 ft. | 6400 lbs | - | 2027461 |
| 20 ft. | 9300 lbs | - | 2027470 |
| 20 ft. | 11500 lbs | - | 2027475 |

■ Color Yellow

SpanSet, Inc.
 3125 Industrial Drive
 Sanford, NC 27331
 United States of
 America
 800-334-7505
 info@spanset.com
 www.spanset.com



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet, Inc. - USA

**SpanSet
 Certified
 Safety**

- Temperature Range -40°C bis +100°C
- Packaging Unit (PU) Content 1

