



### Twintex – Stage Sling

Ideal for inconspicuous suspension of sound and lighting equipment

Item Name short	Weight Net [lbs]	WLL Vertical [lbs]	Length [ft.]	WLL Choker [lbs]	WLL 90° Basket lbs [lbs]	Weight per Foot [lbs/ft]	Minimum Length [ft.]
SS30X3	0.9	2600	3	2100	5200	0.3	-
SS30X4	1.2	2600	4	2100	5200	0.3	-
SS60X3	1.2	5300	3	4200	10600	0.4	1.5
SS60X4	1.6	5300	4	4200	10600	0.4	1.5
SS30X6	1.8	2600	6	2100	5200	0.3	-
SS30X8	2.4	2600	8	2100	5200	0.3	-
SS60X6	2.4	5300	6	4200	10600	0.4	1.5
SS60X8	3.2	5300	8	4200	10600	0.4	1.5

Item Name short	Approx. Width At Load [in]	Approx. Body Diameter Relaxed [in]
SS30X3	1.375	0.5
SS30X4	1.375	0.5
SS60X3	1.68	0.62
SS60X4	1.68	0.62
SS30X6	1.375	0.5
SS30X8	1.375	0.5
SS60X6	1.68	0.62
SS60X8	1.68	0.62

### ORDER NUMBERS

Length	2600 lbs	5300 lbs
3 ft.	2024359	2012780
4 ft.	2024360	2024357
6 ft.	2024361	2013988
8 ft.	2024362	2024358

- **Main Material** Polyester
- **Color** Black
- **Temperature Range** -40°C bis +100°C
- **Packaging Unit (PU) Content** 1

**SpanSet, Inc.**  
3125 Industrial Drive  
Sanford, NC 27331  
United States of America  
800-334-7505  
info@spanset.com  
www.spanset.com



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet, Inc. - USA

**SpanSet  
Certified  
Safety**